

CITIZEN

High resolution 400 dpi printing

CLP7401 - 400 dpi



Citizen's CLP label printers are synonymous with ease of use, performance and reliability. These are the most important design considerations when Citizen develops any barcode printer.

Our 400 dpi CLP 7401 printer continues these concepts with the ability to print on the smallest of labels suitable for PCBs or component manufacturing. With the standard high resolution media sensor, labels just 2.5mm (0.1 inches) can be produced.

Finally, users have no need to wonder whether our label printers are correctly set-up and ready to print. The LCD control panel displays easy-to-understand messages about the status of the printer.



Technical Specification

	CLP 7401
Technology	Thermal transfer and direct thermal
Resolution (approx)	406 dpi, 16 dots/mm
Print speed (max)	4 inches/second, 100 mm/s
Fonts TrueType download	1 Scalable, 8 Bitmap Supported as standard
Media types	Roll or fanfold media; continuous or perforated; die-cut labels, tags & tickets
Media sensing	Label gap, notch or reflective
Media sensors	High resolution fixed and adjustable
Media width (min-max) Media roll size (max) Media thickness	0.75 - 4.65 inches, 19 - 118 mm 8 inches, 200 mm (internal) 0.0025-0.01 inches, 0.635-0.254 mm
Print width (max, 400dpi)	4.1 inches, 104 mm
Print length (max) Label length (min)	10 inches, 254 mm 0.10 in, 2.54 mm
Ribbon type Ribbon length	Wax, wax-resin or resin type, ink out 360m or 74mm/3" outside diameter
Interfaces Parallel RS232C USB Ethernet WiFi	Standard Standard Optional External Optional External Optional External
Case type User interface	Heavy duty metal LCD, 3 buttons + 2 LEDs
User memory Flash expansion	2 Mb 4 Mb
Windows drivers Label design software	Yes, from dealer or web site Yes, from dealer
Options & accessories	Autocutter Peeler External rewinders Network interface, see above Flash memory card, see above
Size (WxDxH) Weight (approx)	260x452x256mm, 10.2x17.8x10.1" 12.5 kg, 27.5 lbs

weitere Informationen erhalten Sie bei:



www.flexicom.de

FLEXICOM GmbH
An der Strusbek 30
D-22926 Ahrensburg
Telefon: 04102 / 46 16 50
Telefax : 04102 / 46 16 25
e-mail: service@flexicom.de

High resolution 400 dpi printing

Easy-to-use, easy-to-install clamshell mechanism

Parallel & serial standard; Network and WiFi options

Heavy duty metal case for durability

Better. Believe It.®

© All trademarks are acknowledged. Errors & omissions excluded.
Note: These specifications are subject to change without notice.
Copyright © Citizen Systems Europe 2003 7401-e1-1003