

# Product Information

Double coated tape

## Flexicom FX8811-T

### Application and Product Composition

Double coated film tape FX8811-T is designed for use in high-speed mail processing systems to affix plastic cards to (personalised) forms.

The clear polyester tape feature a permanent adhesive on the face side and a removable adhesive on the back side (exterior of roll). The low-tack adhesive is covered by liner and the high-tack adhesive is exposed.

Plastic cards can be removed from the low-tack adhesive without adhesive residue.

### Technical Data

Adhesive type:	removable acrylic pressure-sensitive adhesive (low-tack side) medium firm acrylic pressure-sensitive adhesive (high-tack side)
Adhesive carrier:	polyester film, clear, 0.075 mm
Release liner:	paper
Approximate Thickness:	0.07 mm (release liner) 0.13 mm (tape including adhesive)
Adhesion to steel: (AFERA 4001)	<1 N/25 mm (low-tack adhesive) 12 N/25 mm (high-tack adhesive)
Temperature:	15° to 25° C operating range, 120° C maximum
U.V. Resistance:	good
Shelf live: humidity).	12 month (stored in original packaging at 20°C and 50% relative
Stock item:	Rolls, 38 mm x 147 m, 10 rolls per carton

### Further Information:

Flexicom Identification Technologies, An der Strusbek 30, D-22926 Ahrensburg, Germany  
Phone: +49 (0) 4102 / 4616-0, Fax: +49 (0) 4102 / 4616-60  
e-mail: [service@flexicom.de](mailto:service@flexicom.de), Internet: [www.flexicom.de](http://www.flexicom.de)

July 2003